

# G-MINI<sup>®</sup> COMPACT PUMP

Small size. Big value. Huge impact.



PROVEN QUALITY. LEADING TECHNOLOGY.

Make the most of your space, budget and machines. The new full-featured G-Mini offers reliable lubrication in a small footprint to fit more types of machines. Use it to simplify everyday maintenance, extend life cycles and optimize uptime. It's rugged and tough, perfect for handling the 24/7 rigors of any job, big or small. Best of all, it comes with a modest price tag – boosting your productivity and profitability.

**FOLLOWER PLATE AND STIR PADDLE**

Available in 0.5 liter and 1 liter reservoirs.

**PATENT-PENDING HEATER OPTION**

Built-in heater option automatically turns on at 23°F (-5°C), allowing NLGI #2 grease to pump down to -40°F (-40°C).

**M12 INPUT**

M12 cycle or proximity switch input standard on all pumps with a controller.

**POWER AND LOW LEVEL OPTIONS**

CPC or DIN-style connectors make for easy, no hassle installations.



**MULTIPLE RESERVOIR OPTIONS**

0.5 liter, 1 liter and 2 liter grease capacity.

**UP TO TWO PUMP ELEMENTS**

0.18 in<sup>3</sup>/min (3 cm<sup>3</sup>/min) 4,100 psi (280 bar).

**OPTIONAL CONTROLLER**

**No Controller:** Pair with either an external controller or a PLC.

**Controller:** Easy-to-program controller can be utilized for both time-based and cycle-based systems and provides low-level alert and alarm.

**RUGGED CONSTRUCTION**

Designed to withstand the harshest of environments; IP69K rated.

**TYPICAL APPLICATIONS**

- Wind energy
- Industrial
- Off-road / on-road mobile equipment



<b>SPECIFICATIONS</b>	Power source	12 VDC or 24 VDC
	Fluids handled	Grease NLGI 000 to #2
	System	Pump to point or series progressive
	Operating temperature	-40°F to 158°F (-40°C to 70°C)
	Reservoir size	0.5 L / 1 L / 2 L
	Control option	No control, controller (time or cycle)
	Pump elements	Up to 2
	Output pressure	4,100 psi (280 bar)
	Pump output	0.18 in <sup>3</sup> /min (3 cm <sup>3</sup> /min)
	Pump outlet	1/4-18 NPSF, mates with 1/4-18 NPT male fittings
Protection grade	IP69K	
Instruction Manual	3A6714	



# Designed for You to Succeed

## PUMPS

G-Mini pumps **do not** come with power cables. See Accessories below for power cable options.

CONTROLLER OPTION	VOLTAGE	RESERVOIR SIZE	HEATER	FOLLOWER PLATE	PART NUMBER		DESCRIPTION
					POWER INPUT		
					CPC	DIN	
No Controller	12V	0.5 L	No	Yes	25R809	25R829	0.5 Liter, 12 Volt G-Mini Pump with follower plate
		1 L	No	Yes	25R802	25R822	1 Liter, 12 Volt G-Mini Pump with follower plate
			No	No	25R812	25R816	1 Liter, 12 Volt G-Mini Pump
	24V	2 L	No	No	25R832	25R836	2 Liter, 12 Volt G-Mini Pump
		0.5 L	No	Yes	25R807	25R827	0.5 Liter, 24 Volt G-Mini Pump with follower plate
			No	Yes	25R800	25R820	1 Liter, 24 Volt G-Mini Pump with follower plate
			No	No	25R811	25R815	1 Liter, 24 Volt G-Mini Pump
2 L	No	No	25R831	25R835	2 Liter, 24 Volt G-Mini Pump		
Controller	12V	0.5 L	No	Yes	25R810	25R830	0.5 Liter, 12 Volt G-Mini Pump with controller and follower plate
		1 L	No	Yes	25R803	25R823	1 Liter, 12 Volt G-Mini Pump with controller and follower plate
			Yes	Yes	25R806	25R826	1 Liter, 12 Volt G-Mini Pump with controller, heater and follower plate
			No	No	25R814	25R818	1 Liter, 12 Volt G-Mini Pump with controller
	2 L	No	No	25R834	25R838	2 Liter, 12 Volt G-Mini Pump with controller	
	24V	0.5 L	No	Yes	25R808	25R828	0.5 Liter, 24 Volt G-Mini Pump with controller and follower plate
		1 L	No	Yes	25R801	25R821	1 Liter, 24 Volt G-Mini Pump with controller and follower plate
			Yes	Yes	25R804	25R824	1 Liter, 24 Volt G-Mini Pump with controller, heater and follower plate
			No	No	25R813	25R817	1 Liter, 24 Volt G-Mini Pump with controller
		2 L	No	No	25R833	25R837	2 Liter, 24 Volt G-Mini Pump with controller

## ACCESSORIES

Additional accessories can be found in the Graco Automatic Lubrication Equipment (ALE) Buyer's Guide (p/n 340821).

PART NUMBER	DESCRIPTION
127783*	3-Wire CPC Power Cable
127780*	5-Wire CPC Power Cable
16U790*	DIN Connector Power or Low Level Cable
25C981	12V Manual Run Button (5-Wire CPC power cable required)
25C982	24V Manual Run Button (5-Wire CPC power cable required)
26C825	Direct Mount CSP Bracket (not compatible with 2L reservoir)
26C826	Wide Mount Bracket – allows for drop-in replacement of competition (not compatible with 2L reservoir)
17L879	Graco CSP Solid State Proximity Switch (DC PNP)
17R703	1 ft Proximity Switch Cable, M12 female straight to M12 male straight
124333	16.5 ft Proximity Switch Cable, M12 female straight to M12 male straight
26C822	Compact cycle switch with 9.5 in (24 cm) cable and M12 connector, mates to G-Mini Controller**
26C823	Compact cycle switch with 6.5 ft (5 m) cable, requires M12 connector 124594 to use with G-Mini Controller**
26A910	4,000 PSI Pressure Relief Kit (1/4 NPT to 1/8 NPT reducer bushing, 1/8 NPT Tee-fitting, 4,000 PSI Pressure Relief Valve)
26C947	Pump Element Kit (add a second pump element or replace existing)
24M644	High Capacity Fill Stud with Dust Cover
121474	Mating Coupler for 24M644 Fill Stud
247886	Manual Fill Pump – fits 5 gallon or 35 lb pail, includes 121474 (requires 24M644)

\*G-Mini pumps do not come with power cables. A power cable is required for installation.

\*\*Compact cycle switches mount to the Cycle Indicator Pin on a CSP valve; not compatible with "no indicator" valves.





Every Graco purchase comes  
with A+ Customer Service.

Questions?  
Call (800) 533-9655

**For more information visit [graco.com](http://graco.com)**