

HUSKY® 3250

Three-inch high-flow air-operated double diaphragm pump

TACKLE TOUGH TRANSFER JOBS

Transfer up to 250 gpm, including high viscosity materials.

PROVEN RELIABILITY

Based on Graco diaphragm pump platform

BUILT TO LAST

Heavy duty design offers long life, increased productivity and lower overall cost of ownership.

EASY MAINTENANCE

Fewer parts than industry peers with an externally accessible air valve for fast and easy service.





THERE ARE NO EQUALS



Husky 3250 air-operated double diaphragm pumps are loaded with features to help you get the job done right, every time. Graco pumps provide process solutions for numerous abrasive and corrosive applications.



RUGGED CONSTRUCTION

Heavy-duty design for long life

• Four bolt joint deisgn provides even sealing pressure for leak-free operation

MODULAR AIR VALVE

Stall-resistant, efficient operation

 Quick replacement feature with easy four-bolt deisgn

PILOT VALVES

Spring loaded for fast change over

• Externally serviceable

HIGH PERFORMANCE

Up to 250 gallons per minute

• 125 psi

THE GRACO AIR VALVE - SIMPLE BY DESIGN

Built to save you money

- · Fast operating, non-stalling
- Consumes up to 30% less energy
- Externally serviceable in about 5 minutes
- Requires no lubrication, no oilers needed
- Modular with only 13 parts, including the housing





CONTACT US FOR DEMOS OR MORE INFO

Scan the QR code or visit **www.graco.com/pumphouse** to arrange a live or online demonstration or call **866-348-3188** for more information

©2023 Graco Inc. 3H0023EN Rev. A 8/24 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. For more information on Graco's intellectual property, see www.graco.com/patent or www.graco.com/trademarks