## G3<sup>™</sup> HAMMER PUMPS

GRACO

Ideal for Hydraulic Breaker/Hammer Lubrication



Extend the life of your hydraulic hammer/breaker tools and provide a breakthrough for your budget. The new G3 Hammer Pump offers convenient top fill access, enabling chisel paste to be quickly added to the reservoir to avoid halting operations.

Designed for harsh, high vibration environments, the G3 Hammer Pump ideally handles high shock hammer/breaker applications with ease. With precision engineered pump elements based on our industry-leading G3 platform, this pump keeps up with the work you do, increasing both productivity and your bottom line.



#### **TYPICAL APPLICATIONS**

- Hydraulic breakers/hammers



Power source 18-30 VDC; 2.5A current, 60W, inrush/locked rotor 6A Fluids handled Chisel Paste, NLGI #000 to #2 Greases				
00 - matter than 1 - matter th	Chisel Paste, NLGI #000 to #2 Greases			
Operating temperature -40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)			
Reservoir size 4 Liter 8 Liter				
Control option Control pump via external control method				
Pump elements Ships with one pump element, add up to two additional pump elements				
Output pressure 5,100 psi (35.1 MPa, 351.6 bar)	5,100 psi (35.1 MPa, 351.6 bar)			
Pump output 0.25 in <sup>3</sup> /min (4 cm <sup>3</sup> /min) per pump element	0.25 in³/min (4 cm³/min) per pump element			
Pump outlet 1/4-18 NPSF, Mates with 1/4-18 NPT male fittings	1/4-18 NPSF, Mates with 1/4-18 NPT male fittings			
Protection grade IP69K	IP69K			
Instruction Manual 332291	332291			

96G278 133789 96G279 133791

# **DESIGNED FOR YOU TO SUCCEED**

#### **G3 24 VDC HYDRAULIC BREAKER/HAMMER CHISEL PASTE LUBRICATION PUMPS**

PART NUMBER	DESCRIPTION
96G278	4 Liter, 5-pin CPC Cable
96G279	8 Liter, 5-pin CPC Cable
133789	4 Liter, External Low Level, 2 DIN Cables
133791	8 Liter, External Low Level, 2 DIN Cables

#### **ACCESSORIES**

PART NUMBER	DESCRIPTION
26A910	4,000 psi kit (1/4 NPT to 1/8 NPT reducer bushing, 1/8 NPT tee-fitting, 4,000 psi pressure relief valve)
26C030	5,000 psi kit (1/4 NPT to 1/8 NPT reducer bushing, 1/8 NPT tee-fitting, 5,000 psi pressure relief valve)
571041	Replacement pump element
571063	Output union kit – 2 pump elements
571026	Output union kit – 3 pump elements
125910	G3 pump mounting L-bracket









### **OUR BRAND PROMISE TO YOU**

Since 1926, innovation, quality and A+ Service have been at the centre of Graco.

## **Experience Innovation**

Our focus on innovation results in products and equipment that lead the industry with technologically-advanced features, pioneering design, high performance and unparalleled reliability. In short, innovation is how you get better products!

## **Building Quality**

You're investing in high-quality products built to last for years of reliable service. Moreover, we partner with our customers to better understand how you're deploying our products in the field, then use your experiences to improve performance and durability.



## A+ service, every time

You'll see A+ Service in action when you contact any of our support services options no matter where you are in the world. We'll listen to your situation and work methodically to resolve it as quickly as we can. We are guided by a mindset of integrity and a customer service view centred on collaboration and relationships, not transactions.



We're here to answer questions and help address your needs:

www.graco.com/contact

Graco is certified ISO 9001.