Accessory

GLC X to



Compact Dyna-Star[®] Wiring Harness

3A7049A

ΕN

Wiring harness for connecting a GLC X Controller to a Compact Dyna-Star system. For professional use only.

Part No. 26A883

(Power 3 foot length, Signal 3 foot length)



Important Safety Instructions

For complete warnings and instructions refer to the Compact Dyna-Star Electric Pump instruction manual.



3A6941 - Compact Dyna-Star Electric Pump 3A7031- GLC X Lubrication Controller



Connections

Table 1: GLC X Controller Wiring Harness Kit P/N 26A883

Cable	GLC X PIN	CDS PIN	AWG	Color	Function
Signal	1	4	16	Red	Pump/Motor
Signal	2	9	18	White	Auxiliary/Alarm (Vent Valve)
Signal	3	5	16	Black	GND (Pump/Motor)
Signal	4	7	18	Yellow	Sensor Power 1 (Pressure)
Signal	5	1	18	Orange	Sensor Power 2 (Low Level)
Power	6	N/A	16	White	Voltage Source
Signal	7	10	18	Black	GND (Vent Valve)
Signal	8	2	18	Green	GND (Low Level)
Signal	9	3	18	Brown	Input 2 (Low Level)
Power	10	N/A	16	Black	Voltage Source Ground
Signal	11	11	18	Slate	Input 3 (Cycle)
Signal	12	12	18	Violet	Input 4 (Machine Count)
Signal	13	6	18	Green	GND (Pressure)
Signal	14	8	18	Blue	Input 1 (Pressure)

CONNECTORS: TE 776273-1 (GLC X)

TE DT06-12SB (CDS)

Graco Information

For the latest information about Graco products, visit www.graco.com.

For patent information, see www.graco.com/patents.

TO PLACE AN ORDER, contact

Phone: 612-623-6928 or Toll Free: 1-800-533-9655, Fax: 612-378-3590

All written and visual data contained in this document reflects the latest product information available at the time of publication.

Graco reserves the right to make changes at any time without notice.

Original instructions. This manual contains English. MM 3A7049

Graco Headquarters: Minneapolis International Offices: Belgium, China, Japan, Korea

GRACO INC. AND SUBSIDIARIES • P.O. BOX 1441 • MINNEAPOLIS MN 55440-1441 • USA Copyright 2019, Graco Inc. All Graco manufacturing locations are registered to ISO 9001.